

# Bosch 26<sup>eco+</sup> Specifications

|  |  |
|--|--|
| <b>Part Number</b>                                     | BC2600RA   |
| <b>Installation</b>                                    | External   |
| <b>Ignition</b>  | Electronic   |
| <b>L/min (25°C rise)</b>                               | 26   |
| <b>No. of bathrooms</b>                                | 2-3  |
| <b>Min. operating inlet water pressure (kPa)</b>       | 200  |
| <b>Max. inlet water pressure (kPa)</b>                 | 1000   |
| <b>Mj/H</b>  | 178 MJ/hr  |
| <b>Star Rating</b>                                     | 6.9  |
| <b>Temperature Range</b>                               | Factory set at 55°C  |
| <b>Min. Flow (L/Min)</b>                               | 2.5  |
| <b>Min. constant water pressure for Max flow (kPa)</b> | 200  |
| <b>Antifrost</b>                                       | Standard   |
| <b>Gas Type</b>  | NG/LPG   |
| <b>Electrical Supply</b>                               | 230 - 240 VAC 50 Hz (10amp weatherproof power point required within 500mm of the unit) |
| <b>Temperature Controller</b>                          | Up to 4 temperature controllers can be installed (Premium & Sub Controllers only)      |
| <b>Unit Height x Width x Depth (mm)</b>                | 600 x 350 x 260  |
| <b>Carton Weight (kg)</b>                              | 32   |

## Warranty

|                                   |          |
|-----------------------------------|----------|
| <b>Parts &amp; Labour</b>         | 3 Years  |
| <b>Heat Exchanger (part only)</b> | 10 Years |

## Pipe Connection Sizes

|                         |             |
|-------------------------|-------------|
| <b>Natural Gas</b>      | 20mm (3/4") |
| <b>LP Gas</b>           | 20mm (3/4") |
| <b>Cold Water</b>       | 20mm (3/4") |
| <b>Hot Water</b>        | 20mm (3/4") |
| <b>Condensate Drain</b> | 15mm (1/2") |